

BIJLARD 0099 GLUE SPRAY CLASSIC



PRODUCT DESCRIPTION

Is a spray able contact adhesive based on synthetic rubber. The adhesive can be used in a wide variety of applications like:

- carpet, carpet-tiles, underpadding, clothing;
- cork, rubber;
- plastic and foams (also in flakes), seats, cushions etc.
- cardboard, paper (closing of boxes and bags);
- textile, felt;
- polystyrenfoam;
- posters, reproductions;
- insulation-materials.

DIRECTIONS FOR USE

Surfaces must be dry and free from dust. Shake can well before use. Spray from a distance of approx. 25 cm.

Permanent bond: Apply a thin layer of adhesive on both surfaces. After a drying time of 2 - 5 minutes, the surfaces must be joined together. The maximum open time is 45 minutes.

Non permanent bond: Apply an equal thin layer on one of the surfaces. Let it dry for a short time before joining.

This bond can be taken apart without damaging the surfaces. To keep nozzle clear after use, hold the aerosol upside down and push button until no adhesive comes out anymore.

TECHNICAL INFORMATION

Based on : synthetic SBR-rubber in solution.

Specific weight : 0.75 ± 0.02 Kg/L.

Solids contents : 23.5 ± 0.5%.

Physical form : aerosol.

Viscosity : 50 - 200 mPa.s (+20°C).

Colour : milky white.

Drying time : approx. 5 min. (+20°C).

Open time : max.45 min.

Heat resistance : +80°C tested

Propellant : propane/butane (no CFC).

SHELF LIFE

1 year at +20°C.

CLEANING

VERDUNNER.

PACKAGING

500 ml aerosol.

Our processing advice is based on extensive research and practical experience. We can accept no liability for the results obtained and / or any damage resulting from the use of this product because of the wide range of materials and circumstances in which the glue is used. Nevertheless we would be pleased to advise you.

BIJLARD®
PROFESSIONAL ADHESIVES